

TURNING TOOLS

PCBN/PCD TURNING





Contents

PCBN/PCD Turning F

PCBN/PCD Turning Inserts Identification System	604
Application Summary of PCBN Grades	606
Application Summary of PCD Grades	607
Range of PCBN and PCD Turning Inserts	608
PCBN Inserts (Negative)	609
PCBN Inserts (Positive)	612
PCD Insert (Negative)	615
PCD Inserts (Positive)	617
Recommended Cutting Datas	623

F

PCBN/PCD TURNING



PCBN/PCD Turning Indexable Inserts Identification System

Symbol	Shape	Corner Angle	Figure
H	Hexagon	120°	
O	Octagon	135°	
P	Pentagon	108°	
S	Square	90°	
T	Triangle	60°	
C		80°	
D	Rhombic	55°	
V		35°	
W	Trigon	80°	
L	Rectangle	90°	
A	Rectangle	85°	
R	Round	--	

① Shape Symbol

Symbol	Corner Angle
A	3°
B	5°
C	7°
D	15°
E	20°
F	25°
G	30°
N	0°
P	11°
O	Others

② Relief Angle Symbol

Symbol	Tolerance(mm)			Tolerance(inch)		
	Corner Height(m)	Thickness (S)	I.G.dia. (Ød)	Corner Height(m)	Thickness (S)	I.G.dia. (Ød)
A	±0.005	±0.025	±0.025	±0.0002	±0.001	±0.001
F	±0.005	±0.025	±0.013	±0.0002	±0.001	±0.0005
C	±0.013	±0.025	±0.025	±0.0005	±0.001	±0.001
H	±0.013	±0.025	±0.013	±0.0005	±0.001	±0.0005
E	±0.025	±0.025	±0.025	±0.001	±0.001	±0.001
G	±0.025	±0.13	±0.025	±0.001	±0.005	±0.001
J	±0.005	±0.025	±0.05~0.13	±0.0002	±0.001	±0.002~0.005
K	±0.013	±0.025	±0.05~0.13	±0.0005	±0.001	±0.002~0.005
L	±0.025	±0.025	±0.05~0.13	±0.001	±0.001	±0.002~0.005
M	±0.08~0.18	±0.13	±0.05~0.13	±0.003~0.007	±0.005	±0.002~0.005
N	±0.08~0.18	±0.025	±0.05~0.13	±0.003~0.007	±0.001	±0.002~0.005
U	±0.13~0.38	±0.13	±0.08~0.25	±0.005~0.015	±0.005	±0.003~0.01

③ Tolerance Symbol

(1)

(2)

(3)

(4)

(5)



(1)

(2)

(3)


(4)


(5)


④ Hole/Chipbreaker Symbol				
Symbol	Hole	Hole Shape	Chipbreaker	Shape
N	Without	—	Without	
R			Single-sided	
F			Double-sided	
A	With Hole	With Hole	Without	
M			Single-sided	
G			Double-sided	
W	With	With Hob and One Countersink 40°~60°	Without	
T			Single-sided	
Q			Without	
U	With	With Hob and Two Countersinks 40°~60°	Double-sided	
B			Without	
H			Single-sided	
C	With	With Hob and Two Countersinks 70°~90°	Without	
J			Double-sided	
X			—	—

⑤ Edge Length Symbol (ISO) (mm)										I.C.Size (mm)
	P	S	C	W	T	D	E	F	K	
	03	3.97	03	4.0		06	6.9	4	4.8	
	04	4.76	04	4.8		08	8.2	5	5.8	
05	5	--	--	--	--	--	--	--	--	5
	05	5.56	05	5.6	03	3.8	09	9.6	6	6.8
06	6	--	--	--	--	--	--	--	--	6
	06	6.35	06	6.5	04	4.3	11	11	7	7.8
	07	7.94	08	8.1	05	5.4	13	13.8	9	9.7
08	8	--	--	--	--	--	--	--	--	8
09	9.525	9	9.525	9	9.7	06	6.5	16	16.6	16
10	10	--	--	--	--	--	--	--	--	10
12	12	--	--	--	--	--	--	--	--	12
12	12.7	12	12.7	12	12.9	08	8.7	22	22	15
15	15.875	15	15.875	16	16.1	10	10.9	27	27.5	19
16	16	--	--	--	--	--	--	--	--	16
19	19.05	19	19.05	19	19.3	13	13	33	33	23
20	20	--	--	--	--	--	--	--	--	20
	22	22.225	22	22.6		38	38.5	27	27.1	
25	25	--	--	--	--	--	--	--	--	25
25	25.4	25	25.4	25	25.8		44	44	31	25.4
31	31.75	31	31.75	32	32.2		55	55	38	38.8
31	32	--	--	--	--	--	--	--	--	32

PCBN/PCD Turning Indexable Inserts Identification System

	
Symbol	Corner-R (mm)
GN	0°
GB	5°
GC	7°
GT	10°
(10) PCD Rake Angle	



(6) Thickness		(7) Corner Rc Symbol	(8) Tips	(9) Number of transpositions	(10) Geometry
Symbol	Thickness	Symbol	Symbol	Item	Number of transpositions
01	1.59			1	1
02	2.38			2	2
T2	2.78			3	3
03	3.18			4	4
T3	3.97			6	6
04	4.76			8	8
05	5.56				
06	6.35				
07	7.94				
09	9.52				
		Symbol	Application		
		00	0.03		
		02	0.2		
		04	0.4		
		08	0.8		
		12	1.2		
		16	1.6		
		20	2.0		
		24	2.4		
		28	2.8		
		32	3.2		
		(空)	None		

PCBN Grade Application

Workpiece Material		Turning Insert	Recommended Grade	Recommended Cutting Speed (m/min)	ISO	Application Range
K	Gray cast iron	Continuous Cutting		BKN115P	400-1500	K01 K10 K20 K30 K40
		Interrupted Cutting		BKC120P	200-500	BKN115P BKC120P <small>NEW</small>
S	Powder Metallurgy	Continuous Cutting		BSN115P	50-300	S01 S10 S20 S30 S40
		Interrupted Cutting				BSN115P
H	Hardened Material	Continuous Cutting		BHC 115P	100-220	H01
		Medium Interrupted Cutting		BHC 125P	100-200	H10 H20 <small>NEW</small>
		Heavy Interrupted Cutting		BHC 135P	50-130	H30 H40 <small>NEW</small> <small>NEW</small> <small>NEW</small>

Continuous Cutting for hardened material Coated PCBN Grade-BHC115P

	AITIN Coating	The latest AITIN+coating Excellent heat resistance and oxidation resistance
	AITIN Coating	Ultra – fine CBN substrate Excellent wear resistance and red hardness

Continuous Cutting for hardened material Coated PCBN Grade-BHC125P

	AITIN Coating	The latest AITIN+coating Excellent heat resistance and oxidation resistance
	AITIN Coating	Mixed Crystal CBN Substrate Both wear resistance and impact resistance

Heavy Interrupted Cutting for hardened material Coated PCBN Grade-BHC135P


	AITIN Coating	The latest AITIN+coating Excellent heat resistance and oxidation resistance
	AITIN Coating	High ratio CBN substrate Excellent impact resistance and chemical stability

PCBN Grade Application

Workpiece Material	Turning Insert	Recommended Grade	Recommended Cutting Speed (m/min)	ISO	Application Range
N	Non-ferrous metal	Continuous Cutting	DNN105P	N01	DNN105P
			DNN120P		DNN120P
			DNN125P	N10	
		Interrupted Cutting	DNN130P	N20	DNN125P
			DNN135P		DNN130P
	Non-metallic material	Continuous Cutting	DNN105P	N30	DNN135P
			DNN120P		
		Interrupted Cutting	DNN125P		
			DNN130P	N01	
			DNN135P	N10	
	Composite material	Continuous Cutting	DNN130P	~3000	N20
			DNN135P		N30
		Interrupted Cutting	DNN130P	300~1000	DNN30P
			DNN135P		DNN35P

Features&Usage of PCD Grade

Grade	Advantages	Purpose
DNN105P	High density sintered ultra-fine diamond material contribute to the highest wear resistance and collapse resistance, with superior sharpness.	Mainly used in the processing of medium and low silicon aluminium alloy, copper and copper alloy, cemented carbide and ceramic pre-sintered billet and other materials.
NEW DNN120P	Fine-grained diamond material with good machinability and wear resistance	Mainly used in the processing of aluminium alloy, copper and copper alloy, pressed film products, hard rubber, carbon and ceramic pre-sintered blanks and other materials.
DNN125P	Medium-sized diamond material, with good wear resistance and discharge performance, good impact resistance, strong versatility	Mainly used in the processing of aluminium alloy, copper and copper alloy, pressed film products, hard rubber, carbon and ceramic pre-sintered blanks and other materials.
DNN130P	High content, mixed size diamond material, with excellent wear resistance, high impact strength, good surface quality	It is mainly used for milling of high aluminium alloy, processing of carbon fibers and glass fibers.
DNN135P	Large size diamond material, long tool life, high wear resistance, general surface finish	Mainly used for rough turning and intermittent processing of aluminum alloy, MMC, cemented carbide and other wear-resistant materials with silicon content greater than 14%.



Range of PCBN Turning Inserts

PCBN (Negative)

Type	Advantages	Rhombic 80°	Rhombic 55°	Triangle 60°	Rhombic 35°	Trigon 80°
Brazed	<ul style="list-style-type: none"> •High precision and longer tool life •Wide range of insert types •High cost performance 					
		CNGA	DNGA	TNGA	VNGA	WNGA
		P609	P609	P610	P610	P611

PCBN (Positive)

Type	Advantages	Rhombic 80°	Rhombic 55°	Triangle 60°	Rhombic 35°	Trigon 80°
Brazed	<ul style="list-style-type: none"> •High precision and longer tool life •Wide range of insert types •High cost performance 					
		CCGW	DCGW	TCGW/TPGW	VBGW/VCGW	
		P612	P612	P613	P614	

PCD (Negative)

Type	Advantages	Rhombic 80°	Rhombic 55°	Triangle 60°	Rhombic 35°
Brazed	<ul style="list-style-type: none"> •High precision and longer tool life •Wide range of insert types •High cost performance 				
		CNGA	DNGA	TNGA	VNGA
		P615	P615	P616	P616


PCD (Positive)

Type	Advantages	Rhombic 80°	Rhombic 55°	Triangle 60°	Rhombic 35°	Round 360°
Brazed	<ul style="list-style-type: none"> •High precision and longer tool life •Wide range of insert types •High cost performance 					
		CC□W/CP□W	DC□W	TC□W/TP□W	VC□W	RDEW
		P617	P619	P620	P622	P622

PCBN (Negative)

CNGA

Rhombic 80° with Hole




Ordering code	Flute	Dimensions (mm)					PCBN Grade					
		L	D	S	d ₁	R	BKN15P	BKC120P	BHC115P	BHC125P	BHC135P	BSN115P
CNGA120404L-2	2	2.2	12.7	4.76	5.16	0.4	○	○	●	○	○	○
CNGA120404M-2	2	2.2	12.7	4.76	5.16	0.4	○	○	●	●	○	○
CNGA120408L-2	2	2.2	12.7	4.76	5.16	0.8	○	○	○	○	○	○
CNGA120408M-2	2	2.2	12.7	4.76	5.16	0.8	○	○	●	●	●	●
CNGA120408H-2	2	2.2	12.7	4.76	5.16	0.8	○	○	○	●	○	○
CNGA120412M-2	2	2.2	12.7	4.76	5.16	1.2	○	○	●	●	●	○

● Stock ○ Available upon Order

DNGA

Rhombic 55° with Hole




Ordering code	Flute	Dimensions (mm)					PCBN Grade					
		L	D	S	d ₁	R	BKN15P	BKC120P	BHC115P	BHC125P	BHC135P	BSN115P
DNGA150404L-2	2	2.2	12.7	4.76	5.16	0.4	●	○	●	○	○	○
DNGA150404M-2	2	2.2	12.7	4.76	5.16	0.4	○	○	○	●	○	○
DNGA150408L-2	2	2.2	12.7	4.76	5.16	0.8	○	○	●	○	○	○
DNGA150408M-2	2	2.2	12.7	4.76	5.16	0.8	●	○	○	●	○	●
DNGA150412M-2	2	2.2	12.7	4.76	5.16	1.2	○	○	○	○	○	○
DNGA150604M-2	2	2.2	12.7	6.35	5.16	0.4	○	○	○	○	○	○
DNGA150608M-2	2	2.2	12.7	6.35	5.16	0.8	○	○	○	○	○	○
DNGA150612M-2	2	2.2	12.7	6.35	5.16	1.2	○	○	○	○	○	○

● Stock ○ Available upon Order

PCBN (Negative)

TNGA

Triangle 60° with Hole




Ordering code	Flute	Dimensions (mm)					PCBN Grade					
		L	D	S	d ₁	R	BKN15P	BKC120P	BHC115P	BHC125P	BHC135P	BSN115P
TNGA160404L-3	3	2.2	9.525	4.76	3.81	0.4	○	○	●	○	○	○
TNGA160404M-3	3	2.2	9.525	4.76	3.81	0.4	○	○	●	●	○	○
TNGA160408L-3	3	2.2	9.525	4.76	3.81	0.8	○	○	●	●	○	○
TNGA160408M-3	3	2.2	9.525	4.76	3.81	0.8	○	○	●	●	●	○
TNGA160408H-3	3	2.2	9.525	4.76	3.81	0.8	○	○	○	●	○	○
TNGA160412M-3	3	2.2	9.525	4.76	3.81	1.2	○	○	○	○	○	○
TNGA160416H-3	3	2.2	9.525	4.76	3.81	1.6	○	○	○	○	●	○

● Stock ○ Available upon Order

VNGA

Rhombic 35° with Hole




Ordering code	Flute	Dimensions (mm)					PCBN Grade					
		L	D	S	d ₁	R	BKN15P	BKC120P	BHC115P	BHC125P	BHC135P	BSN115P
VNGA160404L-2	2	2.2	9.525	4.76	3.81	0.4	○	○	○	○	○	○
VNGA160404M-2	2	2.2	9.525	4.76	3.81	0.4	○	○	○	●	●	○
VNGA160408L-2	2	2.2	9.525	4.76	3.81	0.8	○	○	●	○	○	○
VNGA160408M-2	2	2.2	9.525	4.76	3.81	0.8	○	○	○	●	●	○
VNGA160412M-2	2	2.2	9.525	4.76	3.81	1.2	○	○	●	○	○	○

● Stock ○ Available upon Order

PCBN (Negative)

WNGA

Trigon 80° with Hole



Ordering code	Flute	Dimensions (mm)					PCBN Grade					
		L	D	S	d ₁	R	BKN115P	BKC120P	BHC115P	BHC125P	BHC135P	BSN115P
WNGA080404L-3	3	2.2	12.7	4.76	3.81	0.4	○	○	○	○	○	○
WNGA080404M-3	3	2.2	12.7	4.76	3.81	0.4	○	○	○	●	○	○
WNGA080408L-3	3	2.2	12.7	4.76	3.81	0.8	○	○	○	○	○	○
WNGA080408M-3	3	2.2	12.7	4.76	3.81	0.8	●	○	○	○	●	○
WNGA080408H-3	3	2.2	12.7	4.76	3.81	0.8	○	○	○	●	○	○
WNGA080412M-3	3	2.2	12.7	4.76	3.81	1.2	○	○	○	○	○	○

●Stock ○Available upon Order




●Stock ○Available upon Order

PCBN (Positive)

CCGW

Rhombic 80° with Hole




Ordering code	Flute	Dimensions (mm)					PCBN Grade						
		L	D	S	d ₁	R	BKN115P	BKC120P	BHC115P	BHC125P	BHC135P	BSN115P	
CCGW060202L-2	2	2	6.35	2.38	2.8	0.2	○	○	○	○	○	○	
CCGW060204L-2	2	2	6.35	2.38	2.8	0.4	○	○	●	●	○	○	
CCGW060204M-2	2	2	6.35	2.38	2.8	0.4	○	○	○	○	○	○	
CCGW060208L-2	2	2	6.35	2.38	2.8	0.8	○	○	○	○	○	○	
CCGW060208M-2	2	2	6.35	2.38	2.8	0.8	○	○	●	○	○	○	
CCGW09T302L-2	2	2	9.525	3.97	4.4	0.2	○	○	○	○	○	○	
CCGW09T304L-2	2	2	9.525	3.97	4.4	0.4	●	○	●	○	○	○	
CCGW09T304M-2	2	2	9.525	3.97	4.4	0.4	○	○	○	●	●	○	
CCGW09T308L-2	2	2	9.525	3.97	4.4	0.8	○	○	○	○	○	○	
CCGW09T308M-2	2	2	9.525	3.97	4.4	0.8	●	○	●	●	●	○	
CCGW09T308H-2	2	2	9.525	3.97	4.4	0.8	○	○	○	●	○	○	

●Stock ○Available upon Order

DCGW

Rhombic 55° with Hole




Ordering code	Flute	Dimensions (mm)					PCBN Grade						
		L	D	S	d ₁	R	BKN115P	BKC120P	BHC115P	BHC125P	BHC135P	BSN115P	
DCGW070202L-2	2	2	6.35	2.38	2.8	0.2	○	○	○	●	○	○	
DCGW070204L-2	2	2	6.35	2.38	2.8	0.4	○	○	●	●	○	○	
DCGW070204M-2	2	2	6.35	2.38	2.8	0.4	○	○	○	○	○	○	
DCGW070208L-2	2	2	6.35	2.38	2.8	0.8	○	○	○	○	○	○	
DCGW070208M-2	2	2	6.35	2.38	2.8	0.8	○	○	○	○	○	○	
DCGW11T302L-2	2	2	9.525	3.97	4.4	0.2	○	○	○	○	○	○	
DCGW11T304L-2	2	2	9.525	3.97	4.4	0.4	●	○	○	○	○	○	
DCGW11T304M-2	2	2	9.525	3.97	4.4	0.4	○	○	●	●	●	○	
DCGW11T308L-2	2	2	9.525	3.97	4.4	0.8	○	○	○	○	○	○	
DCGW11T308M-2	2	2	9.525	3.97	4.4	0.8	○	○	●	●	●	●	

●Stock ○Available upon Order

PCBN (Positive)

TCGW

Triangle 60° with Hole




Ordering code	Flute	Dimensions (mm)					PCBN Grade				
		L	D	S	d1	R	BKN15P	BKC120P	BHC115P	BHC125P	BHC135P
TCGW110302L-3	3	2	6.35	3.18	3.4	0.2	○	○	○	○	○
TCGW110304L-3	3	2	6.35	3.18	3.4	0.4	●	○	○	○	○
TCGW110304M-3	3	2	6.35	3.18	3.4	0.4	○	○	○	●	○
TCGW110308L-3	3	2	6.35	3.18	3.4	0.8	○	○	○	○	○
TCGW110308M-3	3	2	6.35	3.18	3.4	0.8	○	○	○	○	○

● Stock ○ Available upon Order

TPGW

Triangle 60° with Hole




Ordering code	Flute	Dimensions (mm)					PCBN Grade				
		L	D	S	d1	R	BKN15P	BKC120P	BHC115P	BHC125P	BHC135P
TPGW080202L-1	1	2	4.76	2.38	2.3	0.2	○	○	○	○	○
TPGW080204L-1	1	2	4.76	2.38	2.3	0.4	○	○	○	○	○
TPGW080208L-1	1	2	4.76	2.38	2.3	0.8	○	○	○	○	○
TPGW090202L-3	3	2	5.56	2.38	2.8	0.2	○	○	○	○	○
TPGW090204L-3	3	2	5.56	2.38	2.8	0.4	●	○	○	●	○
TPGW090208L-3	3	2	5.56	2.38	2.8	0.8	●	○	○	○	○
TPGW110202L-3	3	2	6.35	2.38	2.8	0.2	○	○	○	○	○
TPGW110204L-3	3	2	6.35	2.38	2.8	0.4	○	○	○	○	○
TPGW110208M-3	3	2	6.35	2.38	2.8	0.8	○	○	○	○	○
TPGW110302L-3	3	2	6.35	3.18	3.4	0.2	○	○	○	○	○
TPGW110304L-3	3	2	6.35	3.18	3.4	0.4	○	○	○	○	●
TPGW110304M-3	3	2	6.35	3.18	3.4	0.4	○	○	○	○	○
TPGW110308L-3	3	2	6.35	3.18	3.4	0.8	○	○	●	●	○
TPGW110308M-3	3	2	6.35	3.18	3.4	0.8	○	○	○	○	○

● Stock ○ Available upon Order

PCBN (Positive)

VBGW

Rhombic 35° with Hole




Ordering code	Flute	Dimensions (mm)					PCBN Grade					
		L	D	S	d ₁	R	BKN115P	BHN115P	BHC115P	BHC125P	BHC135P	BHC135P
VBGW110302L-2	2	2	6.35	3.18	2.8	0.2	○	○	○	○	○	○
VBGW110304L-2	2	2	6.35	3.18	2.8	0.4	○	○	○	●	○	○
VBGW110308L-2	2	2	6.35	3.18	2.8	0.8	○	○	○	●	○	○
VBGW110308M-2	2	2	6.35	3.18	2.8	0.8	○	○	○	○	○	○
VBGW160402L-2	2	2	9.525	4.76	4.4	0.2	○	○	○	○	○	○
VBGW160404L-2	2	2	9.525	4.76	4.4	0.4	●	○	○	○	○	○
VBGW160408L-2	2	2	9.525	4.76	4.4	0.8	●	○	○	○	○	○
VBGW160408M-2	2	2	9.525	4.76	4.4	0.8	○	○	●	●	○	○

●Stock ○Available upon Order

VCGW

Rhombic 35° with Hole




Ordering code	Flute	Dimensions (mm)					PCBN Grade					
		L	D	S	d ₁	R	BKN115P	BKC120P	BHC115P	BHC125P	BHC135P	BSN115P
VCGW110302L-2	2	2	6.35	3.18	2.8	0.2	○	○	○	○	○	○
VCGW110304L-2	2	2	6.35	3.18	2.8	0.4	●	○	○	○	○	○
VCGW110308L-2	2	2	6.35	3.18	2.8	0.8	○	○	○	○	○	○
VCGW110308M-2	2	2	6.35	3.18	2.8	0.8	●	○	○	○	○	○
VCGW160402L-2	2	2	9.525	4.76	4.4	0.2	○	○	○	○	○	○
VCGW160404L-2	2	2	9.525	4.76	4.4	0.4	○	○	○	○	○	○
VCGW160408L-2	2	2	9.525	4.76	4.4	0.8	○	○	○	○	○	○
VCGW160408M-2	2	2	9.525	4.76	4.4	0.8	○	○	○	●	○	○

●Stock ○Available upon Order

PCD (Negative)

CNGA

Rhombic 80° with Hole




Ordering code	Flute	Dimensions (mm)					PCD Grade				
		L	D	S	d ₁	R	DNN105P	DNN120P	DNN125P	DNN130P	DNN135P
CNGA120404	1	3	12.7	4.76	5.16	0.4	○	○	○	○	○
CNGA120408	1	3	12.7	4.76	5.16	0.8	○	○	○	○	○

●Stock ○Available upon Order

DNGA

Rhombic 55° with Hole




Ordering code	Flute	Dimensions (mm)					PCD Grade				
		L	D	S	d ₁	R	DNN105P	DNN120P	DNN125P	DNN130P	DNN135P
DNGA150404	1	5	12.7	4.76	5.16	0.4	○	○	○	○	○
DNGA150408	1	5	12.7	4.76	5.16	0.8	○	○	○	○	○

●Stock ○Available upon Order

PCD insert(Negative)

TNGA

Triangle 60° with Hole




Ordering code	Flute	Dimensions (mm)					PCD Grade				
		L	D	S	d ₁	R	DNN105P	DNN120P	DNN125P	DNN130P	DNN135P
TNGA160404	1	3	9.525	4.76	3.81	0.4	○	○	○	○	○
TNGA160408	1	3	9.525	4.76	3.81	0.8	○	○	○	○	○

●Stock ○Available upon Order

VNGA

Rhombic 35° with Hole




Ordering code	Flute	Dimensions (mm)					PCD Grade				
		L	D	S	d ₁	R	DNN105P	DNN120P	DNN125P	DNN130P	DNN135P
VNGA160404	1	3	9.525	4.76	3.81	0.4	○	○	○	○	○
VNGA160408	1	3	9.525	4.76	3.81	0.8	○	○	○	○	○

●Stock ○Available upon Order

PCD (Positive)


CC□W

Rhombic 80° with Hole



Ordering code	Flute	Dimensions (mm)					PCD Grade				
		L	D	S	d ₁	R	DNN105P	DNN120P	DNN125P	DNN130P	DNN135P
CCGW060202	1	2.5	6.35	2.38	2.8	0.2	○	○	○	○	○
CCGW060204	1	2.5	6.35	2.38	2.8	0.4	○	○	○	○	○
CCGW060208	1	2.5	6.35	2.38	2.8	0.8	○	○	○	○	○
CCMW060202M	1	2.5	6.35	2.38	2.8	0.2	○	○	○	○	○
CCMW060204M	1	2.5	6.35	2.38	2.8	0.4	○	○	●	○	○
CCMW060208M	1	2.5	6.35	2.38	2.8	0.8	○	○	○	○	○
CCGW09T302	1	3.0	9.525	3.97	4.4	0.2	○	○	○	○	○
CCGW09T304	1	3.0	9.525	3.97	4.4	0.4	●	○	●	○	○
CCGW09T308	1	3.0	9.525	3.97	4.4	0.8	○	○	○	○	○
CCMW09T302M	1	3.0	9.525	3.97	4.4	0.2	○	○	●	○	○
CCMW09T304M	1	3.0	9.525	3.97	4.4	0.4	○	○	●	○	○
CCMW09T308M	1	3.0	9.525	3.97	4.4	0.8	○	○	○	○	○
CCGW120402	1	3.0	12.7	4.76	5.5	0.2	○	○	○	○	○
CCGW120404	1	3.0	12.7	4.76	5.5	0.4	○	○	○	○	○
CCGW120408	1	3.0	12.7	4.76	5.5	0.8	○	○	○	○	○
CCMW120402M	1	3.0	12.7	4.76	5.5	0.2	○	○	○	○	○
CCMW120404M	1	3.0	12.7	4.76	5.5	0.4	○	○	●	○	○
CCMW120408M	1	3.0	12.7	4.76	5.5	0.8	○	○	○	○	○


●Stock ○Available upon Order



PCD (Positive)

CP□W

Rhombic 80° with Hole



Ordering code	Flute	Dimensions (mm)					PCD Grade				
		L	D	S	d ₁	R	DNN105P	DNN120P	DNN125P	DNN130P	DNN135P
CPGW060202	1	2.5	6.35	2.38	2.8	0.2	○	○	○	○	○
CPGW060204	1	2.5	6.35	2.38	2.8	0.4	○	○	○	○	○
CPGW060208	1	2.5	6.35	2.38	2.8	0.8	○	○	○	○	○
CPMW060202M	1	2.5	6.35	2.38	2.8	0.2	○	○	○	○	○
CPMW060204M	1	2.5	6.35	2.38	2.8	0.4	○	○	○	○	○
CPMW060208M	1	2.5	6.35	2.38	2.8	0.8	○	○	○	○	○
CPGW09T302	1	3.0	9.525	3.97	4.4	0.2	○	○	○	○	○
CPGW09T304	1	3.0	9.525	3.97	4.4	0.4	●	○	●	○	○
CPGW09T308	1	3.0	9.525	3.97	4.4	0.8	○	○	○	○	○
CPMW09T302M	1	3.0	9.525	3.97	4.4	0.2	○	○	●	○	○
CPMW09T304M	1	3.0	9.525	3.97	4.4	0.4	○	○	●	○	○
CPMW09T308M	1	3.0	9.525	3.97	4.4	0.8	○	○	○	○	○
CPGW120402	1	3.0	12.7	4.76	5.5	0.2	○	○	○	○	○
CPGW120404	1	3.0	12.7	4.76	5.5	0.4	○	○	○	○	○
CPGW120408	1	3.0	12.7	4.76	5.5	0.8	○	○	○	○	○
CPMW120402M	1	3.0	12.7	4.76	5.5	0.2	○	○	○	○	○
CPMW120404M	1	3.0	12.7	4.76	5.5	0.4	○	○	●	○	○
CPMW120408M	1	3.0	12.7	4.76	5.5	0.8	○	○	○	○	○


●Stock ○Available upon Order



PCD (Positive)


DC□W

Rhombic 55° with Hole



Ordering code	Flute	Dimensions (mm)					PCD Grade				
		L	D	S	d ₁	R	DNN105P	DNN120P	DNN125P	DNN130P	DNN135P
DCGW070204	1	2.5	6.35	2.38	2.8	0.4	○	○	○	○	○
DCMW070204M	1	2.5	6.35	2.38	2.8	0.4	○	○	●	○	○
DCGW11T302	1	3.0	9.525	3.97	4.4	0.2	○	○	○	○	○
DCGW11T304	1	3.0	9.525	3.97	4.4	0.4	●	○	●	○	○
DCGW11T308	1	3.0	9.525	3.97	4.4	0.8	○	○	○	○	○
DCMW11T302M	1	3.0	9.525	3.97	4.4	0.2	○	○	●	○	○
DCMW11T304M	1	3.0	9.525	3.97	4.4	0.4	○	○	●	○	○
DCMW11T308M	1	3.0	9.525	3.97	4.4	0.8	○	○	○	○	○


●Stock ○Available upon Order



PCD (Positive)

TC□W

Triangle 60° with Hole



Ordering code	Flute	Dimensions (mm)					PCD Grade				
		L	D	S	d ₁	R	DNN105P	DNN120P	DNN125P	DNN130P	DNN135P
TCGW080202	1	2.5	4.76	2.38	2.5	0.2	○	○	○	○	○
TCGW080204	1	2.5	4.76	2.38	2.5	0.4	●	○	○	○	○
TCMW080202M	1	2.5	4.76	2.38	2.5	0.2	○	○	●	○	○
TCMW080204M	1	2.5	4.76	2.38	2.5	0.4	○	○	●	○	○
TCGW090202	1	2.5	5.56	2.38	2.5	0.2	○	○	○	○	○
TCGW090204	1	2.5	5.56	2.38	2.5	0.4	○	○	○	○	○
TCMW090202M	1	2.5	5.56	2.38	2.5	0.2	○	○	●	○	○
TCMW090204M	1	2.5	5.56	2.38	2.5	0.4	○	○	●	○	○
TCGW110302	1	3.0	6.35	3.18	2.8	0.2	○	○	○	○	○
TCGW110304	1	3.0	6.35	3.18	2.8	0.4	●	○	○	○	○
TCGW110308	1	3.0	6.35	3.18	2.8	0.8	○	○	○	○	○
TCMW110302M	1	3.0	6.35	3.18	2.8	0.2	○	○	●	○	○
TCMW110304M	1	3.0	6.35	3.18	2.8	0.4	○	○	●	○	○
TCMW110308M	1	3.0	6.35	3.18	2.8	0.8	○	○	○	○	○
TCGW160402	1	3.0	9.525	4.76	4.4	0.2	○	○	○	○	○
TCGW160404	1	3.0	9.525	4.76	4.4	0.4	○	○	○	○	○
TCGW160408	1	3.0	9.525	4.76	4.4	0.8	○	○	○	○	○
TCMW160402M	1	3.0	9.525	4.76	4.4	0.2	○	○	○	○	○
TCMW160404M	1	3.0	9.525	4.76	4.4	0.4	○	○	○	○	○
TCMW160408M	1	3.0	9.525	4.76	4.4	0.8	○	○	○	○	○


●Stock ○Available upon Order



PCD (Positive)

TP □ W

Triangle 60° with Hole



Ordering code	Flute	Dimensions (mm)					PCD Grade				
		L	D	S	d ₁	R	DNN105P	DNN120P	DNN125P	DNN130P	DNN135P
TPGW080202	1	2.5	4.76	2.38	2.5	0.2	○	○	○	○	○
TPGW080204	1	2.5	4.76	2.38	2.5	0.4	○	○	○	○	○
TPMW080202M	1	2.5	4.76	2.38	2.5	0.2	○	○	○	○	○
TPMW080204M	1	2.5	4.76	2.38	2.5	0.4	○	○	●	○	○
TPGW090202	1	2.5	5.56	2.38	2.5	0.2	○	○	○	○	○
TPGW090204	1	2.5	5.56	2.38	2.5	0.4	○	○	●	○	○
TPMW090202M	1	2.5	5.56	2.38	2.5	0.2	○	○	○	○	○
TPMW090204M	1	2.5	5.56	2.38	2.5	0.4	○	○	●	○	○
TPGW110302	1	3.0	6.35	3.18	2.8	0.2	○	○	○	○	○
TPGW110304	1	3.0	6.35	3.18	2.8	0.4	○	○	○	○	○
TPGW110308	1	3.0	6.35	3.18	2.8	0.8	○	○	○	○	○
TPMW110302M	1	3.0	6.35	3.18	2.8	0.2	○	○	○	○	○
TPMW110304M	1	3.0	6.35	3.18	2.8	0.4	○	○	●	○	○
TPMW110308M	1	3.0	6.35	3.18	2.8	0.8	○	○	○	○	○
TPGW160402	1	3.0	9.525	4.76	4.4	0.2	○	○	○	○	○
TPGW160404	1	3.0	9.525	4.76	4.4	0.4	○	○	○	○	○
TPGW160408	1	3.0	9.525	4.76	4.4	0.8	○	○	○	○	○
TPMW160402M	1	3.0	9.525	4.76	4.4	0.2	○	○	○	○	○
TPMW160404M	1	3.0	9.525	4.76	4.4	0.4	○	○	○	○	○
TPMW160408M	1	3.0	9.525	4.76	4.4	0.8	○	○	○	○	○


●Stock ○Available upon Order



PCD (Positive)

VC□W

Rhombic 35° with Hole




Ordering code	Flute	Dimensions (mm)					PCD Grade				
		L	D	S	d ₁	R	DNN105P	DNN120P	DNN125P	DNN130P	DNN135P
VCGW110302	1	3.0	6.35	3.18	2.8	0.2	○	○	○	○	○
VCGW110304	1	3.0	6.35	3.18	2.8	0.4	○	○	●	○	○
VCGW110308	1	3.0	6.35	3.18	2.8	0.8	○	○	○	○	○
VCMW110302M	1	3.0	6.35	3.18	2.8	0.2	○	○	●	○	○
VCMW110304M	1	3.0	6.35	3.18	2.8	0.4	○	○	○	○	○
VCMW110308M	1	3.0	6.35	3.18	2.8	0.8	○	○	○	○	○
VCGW160402	1	3.0	9.525	4.76	4.4	0.2	○	○	○	○	○
VCGW160404	1	3.0	9.525	4.76	4.4	0.4	○	○	●	○	○
VCGW160408	1	3.0	9.525	4.76	4.4	0.8	○	○	○	○	○
VCGW160412	1	3.0	9.525	4.76	4.4	1.2	○	○	○	○	○
VCMW160402M	1	3.0	9.525	4.76	4.4	0.2	○	○	○	○	○
VCMW160404M	1	3.0	9.525	4.76	4.4	0.4	○	○	●	○	○
VCMW160408M	1	3.0	9.525	4.76	4.4	0.8	○	○	○	○	○
VCMW160412M	1	3.0	9.525	4.76	4.4	1.2	○	○	○	○	○

●Stock ○Available upon Order

RDEW

Round 80° with Hole



Ordering code	Flute	Dimensions (mm)			PCD Grade				
		D	S	d ₁	DNN105P	DNN120P	DNN125P	DNN130P	DNN135P
RDEW0803	1	8	3.18	2.94	○	○	○	○	○
RDEW1003	1	10	3.18	4.4	○	○	○	○	○
RDEW1204	1	12	4.76	4.4	○	○	○	○	○

●Stock ○Available upon Order

Recommended Cutting Data

PCBN Tool

ISO	Workpiece Material	Hardness	Cutting Range	Purpose	Geometry	Grade	Min-Optimum-Max		
							Vc(m/min)	ap(mm)	f(mm/rev)
	Gray cast iron	HB200~230	Finishing	General	/	BKN115P	400-600-1500	0.05-0.20-0.50	0.05-0.20-0.40
K	Alloy cast iron	≥HB200	Finishing	General	/	BKN115P	200-400-800	0.05-0.20-0.50	0.05-0.20-0.40
	Powder Metallurgy	QT450~QT700	Finishing	General	/	BKC120P	150-300-500	0.10-0.20-0.50	0.05-0.12-0.3
S	Hardened Material	HRB50~90	Finishing	Continious	/	BSN115P	50-150-300	0.05-0.20-0.5	0.05-0.12-0.30
	Hardened Material	≥HRC50	Finishing	Continious	/	BHC115P	120-150-220	0.05-0.10-0.20	0.05-0.10-0.20
H	Hardened Material	≥HRC50	Roughing-Finishing	General	/	BHC125P	100-130-180	0.05-0.10-0.50	0.05-0.10-0.20
	Hardened Material	≥HRC50	Finishing-Semi-finishing	Interrupted	/	BHC135P	80-100-150	0.05-0.10-0.40	0.05-0.10-0.20

PCD Tool

ISO	Workpiece Material	Vc (m/min)	f(mm/rev)	ap(mm)
N	Aluminum Alloy	~3000	~0.2	~3
	Copper Alloy	~1000	~0.2	~3
	Reinforced plastics	~1000	~0.4	~3
	Wood and inorganic board	~4000	~0.4	-
	Cemented Alloy	10~30	~0.2	~0.5
	Graphite	100~600	~1	~3